



[DCA HOME](#) | [ABOUT DCA](#) | [DCA PROGRAMS](#)



[BCIS Home](#) | [Log In](#) | [Hot Topics](#) | [Submit Surcharge](#) | [Stats & Facts](#) | [Publications](#) | [FBC Staff](#) | [BCIS Site Map](#) | [I](#)



Product Approval
USER: Public User

- ▶ COMMUNITY PLANNING
- ▶ HOUSING & COMMUNITY DEVELOPMENT
- ▶ EMERGENCY MANAGEMENT
- ▶ OFFICE OF THE SECRETARY

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

FL # FL4077-R1
 Application Type Revision
 Code Version 2004
 Application Status Approved
 Comments
 Archived

Product Manufacturer Edco Products, Inc.
 Address/Phone/Email 8700 Excelsior Blvd.
 Hopkins, MN 55343
 (952) 945-2629
 tmankowski@edcoproducts.com

Authorized Signature Tom Mankowski
 tmankowski@edcoproducts.com

Technical Representative Tom Mankowski
 Address/Phone/Email 8700 Excelsior Blvd.
 Hopkins, MN 55343
 (952) 938-6313
 tmankowski@edcoproducts.com

Quality Assurance Representative
 Address/Phone/Email

Category Roofing

Subcategory	Metal Roofing
Compliance Method	Test Report
Testing Lab	Hurricane Test Laboratory, LLC - C
Quality Assurance Entity	Underwriters Laboratories Inc.
Quality Assurance Contract Expiration Date	
Validated By	Terrence E. Wolfe P.E
	<input type="checkbox"/> Validation Checklist - Hardcopy

Certificate of Independence

Referenced Standard and Year (of Standard)	Standard
	AISI
	ASTM A 653
	ASTM A653
	Florida Building Code
	Florida Building Code
	Florida Building Code
	Florida Building Code
	TAS 125
	TAS 125
	UL 1897
	UL 1897
	UL 580

Equivalence of Product Standards
 Certified By

Sections from the Code	1505.3
	1507.5
	Ch. 16
	Ch. 23

Product Approval Method	Method 1 Option B
-------------------------	-------------------

Date Submitted	09/14/2005
Date Validated	09/14/2005

Date Pending FBC Approval 10/01/2005
 Date Approved 10/11/2005

Summary of Products

FL #	Model, Number or Name	Description
4077.1	1270 ArrowLine SS	
<p>Limits of Use (See Other) Approved for use in HVHZ: Approved for use outside HVHZ: Impact Resistant: Design Pressure: +/- Other: Non-HVHZ Maximum Uplift Pressure 104.8 PSF w/clip spacing= 10-inches o.c.; Maximum Uplift 116 PSF w/clip spacing = 8.5-inches; Min. Slope 4:12 Min. 19/32CDX for new construction; Min. 15/32 CDX 4 ply for existing structures. install per manufacturers installation instructions.</p>		<p>Installation Instructions PTID 4077 I 1270-ALineSS-InstallManFL1.pdf PTID 4077 R1 I Eval Report PTID 4077 R1 I FET letter o Verified By: Test Reports PTID 4077 T HTL Test Repo EDCO.pdf</p>

[Back](#) [Next](#)

[DCA Administration](#)
 Department of Community Affairs
 Florida Building Code Online
 Codes and Standards
 2555 Shumard Oak Boulevard
 Tallahassee, Florida 32399-2100
 (850) 487-1824, Fax (850) 414-8436

© 2000-2005 The State of Florida. All rights reserved. [Copyright and Dis](#)
 Product Approval Accepts:



 Click to Verify - This site has chosen a VeriSign SSL Certificate to improve Web site security