



Metro SHINGLE Specification

ISS: 7/9/03 REV: 4/9/2007

| | |
|------------------------------|--|
| Size | Length: 52.00" Cover Length: 50" Width: 10.5" Cover Width: 9.75" 31 pcs/Sq. |
| Accessories | STONE-COATED: Shingle Cap for Ridge & Hip. / Rake Channel X 79". / Z-Bar X 79". / Valley Cover X 79". / Tie-In Metal X 79". / SMART-jack pipe flashing. / SMART-Sleeve pipe covers. / SAMRT-vent ventilator panels. PAINTED: Starter Strip Metal X 120". / Short Course Cleat X 120". / Dbl 'V' Valley 120". / Drip Edge 120". / Side-Wall Underpan metal 120". |
| Protective Coating | *Galvalume® (*Reg. Trademark of BIEC Intl. Inc.) |
| Substrate | Steel — ASTM A-792 |
| Mechanical Properties | Grade 33 |
| Base Metal Thickness | .015" Inches |
| Coating Weight | AZ-50 *Galvalume® |
| Primer | *Galvalume® Plus or pigmented Color Coating |
| Minimum Pitch | 3: 12 (12 Degrees) |
| Weight | 3.6 lbs. Each panel or 112 lbs. / Sq. |
| Pallet Size | 44" W X 55" L X 27" H = Contains 480 Panels & Weighs 2,100 lbs. approximately covering 15.4 Squares approximately. |
| CONCEALED Fasteners | BATTEN-LESS: Panels are installed from the bottom of the roof up to the ridge. Standard install four (4) fasteners per panel through the back horizontal fastening flange on each shingle panel. |
| HVHZ | High Velocity Hurricane Zone areas require special fasteners and in a specific pattern. Refer to Metro's HVHZ install details for more information. |

Best Buy Metals

Toll Free 1-800-728-4010 / Phone 423-479-6382 / Fax 423-728-3066

www.BestBuyMetals.com