



[DCA HOME](#) | [ABOUT DCA](#) | [DCA PROGRAMS](#)



[BCIS Home](#) | [Log In](#) | [Hot Topics](#) | [Submit & Surcharge](#) | [Stats & Facts](#) | [Publications](#) | [FBC Staff](#) | [BCIS Site Map](#) | [I](#)



Product Approval
USER: Public User

- ▶ COMMUNITY PLANNING
- ▶ HOUSING & COMMUNITY DEVELOPMENT
- ▶ EMERGENCY MANAGEMENT
- ▶ OFFICE OF THE SECRETARY

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

FL #	FL10916
Application Type	New
Code Version	2007
Application Status	Approved
Comments	
Archived	<input type="checkbox"/>
Product Manufacturer	Metal Sales Manufacturing Corpora
Address/Phone/Email	7800 State Road 60 Sellersburg, IN 47172 (812) 218-7342 dstermer@metalsales.us.com
Authorized Signature	David Stermer, PE dstermer@metalsales.us.com
Technical Representative	
Address/Phone/Email	
Quality Assurance Representative	
Address/Phone/Email	
Category	Roofing
Subcategory	Metal Roofing

Compliance Method Evaluation Report from a Florida R
Architect or a Licensed Florida Pro
Engineer
 Evaluation Report - Hardcopy R

Florida Engineer or Architect Name who developed the Evaluation Report Bala Sockalingam
Florida License PE-62240
Quality Assurance Entity Keystone Certifications, Inc.
Quality Assurance Contract Expiration Date 12/31/2011
Validated By Yoosef Lavi, P.E.
 Validation Checklist - Hardcopy

Certificate of Independence [FL10916_R0_COI_CertificateIndex](#)

Referenced Standard and Year (of Standard)	Standard	Ye
	UL 1897	19
	UL 580	19

Equivalence of Product Standards Certified By

Sections from the Code

Product Approval Method Method 1 Option D

Date Submitted 07/03/2008
Date Validated 07/15/2008
Date Pending FBC Approval 07/20/2008
Date Approved 09/15/2008

Summary of Products

FL #	Model, Number or Name	Description
10916.1	2.5" Corrugated	26 ga., 21.33" wide through fastened r over plywood deck
Limits of Use Approved for use in HVHZ: No		Installation Instructions FL10916_R0_II_1582_17_D.pdf

<p>Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-86.0 Other: 82.3 psf @ fastener spacing of 36" oc and 86.0 psf @ fastener spacing of 12" oc</p>		<p>Verified By: Bala Sockalingam PE 6 Created by Independent Third Party: Evaluation Reports FL10916 R0 AE EvaluationReport Created by Independent Third Party:</p>
10916.2	5V-Crimp	26 ga., 24" wide through fastened roof plywood deck
<p>Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-100.6 Other: 41.6 psf @ fastener spacing of 36" oc and 100.6 psf @ fastener spacing of 6" oc</p>		<p>Installation Instructions FL10916 R0 II 1582 18 D.pdf Verified By: Bala Sockalingam PE 6 Created by Independent Third Party: Evaluation Reports FL10916 R0 AE EvaluationReport Created by Independent Third Party:</p>
10916.3	Classic Rib	26 ga., 36" wide through fastened roof plywood deck
<p>Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-74.8 Other: 74.8 psf @ fastener spacing of 36" oc</p>		<p>Installation Instructions FL10916 R0 II 1582 19 D.pdf Verified By: Bala Sockalingam 6224 Created by Independent Third Party: Evaluation Reports FL10916 R0 AE EvaluationReport Created by Independent Third Party:</p>
10916.4	Image II	26 ga., 16" wide Concealed fastened roof over plywood deck
<p>Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-85.6 Other: 41.6 psf @ fastener spacing of 24" oc and 85.6 psf @ fastener spacing of 6" oc</p>		<p>Installation Instructions FL10916 R0 II 1582 20 D.pdf Verified By: Bala Sockalingam 6224 Created by Independent Third Party: Evaluation Reports FL10916 R0 AE EvaluationReport Created by Independent Third Party:</p>
10916.5	Stile	26 ga., 39.4" wide through fastened roof plywood deck
<p>Limits of Use</p>		<p>Installation Instructions</p>

<p>Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-100.9 Other: 50.4 psf @ fastener spacing of 36" oc and 100.9 psf @ fastener spacing of 12" oc</p>		<p>FL10916_R0_II_1582_21_D.pdf Verified By: Bala Sockalingam 62244 Created by Independent Third Party: Evaluation Reports FL10916_R0_AE_EvaluationReport Created by Independent Third Party:</p>
10916.6	Vertical Seam	24 ga., 16" wide standing seam roof p plywood deck
<p>Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-43.3 Other: 43.3 psf @ clip spacing of 36" oc</p>		<p>Installation Instructions FL10916_R0_II_1582_22_D.pdf Verified By: Bala Sockalingam 62244 Created by Independent Third Party: Evaluation Reports FL10916_R0_AE_EvaluationReport Created by Independent Third Party:</p>

[Back](#) [Next](#)

[DCA Administration](#)
Department of Community Affairs
Florida Building Code Online
Codes and Standards
 2555 Shumard Oak Boulevard
 Tallahassee, Florida 32399-2100
 (850) 487-1824, Fax (850) 414-8436

© 2000-2005 The State of Florida. All rights reserved. [Copyright and Dis](#)
 Product Approval Accepts:



Click to Verify - This site has chosen a VeriSign SSL Certificate to improve Web site security