Business & Professional Regulation





BCIS Home | Log In | User Registration | Hot Topics | Submit Surcharge | Stats & Facts | Publications | FBC Staff | BCIS Site Map | Links | Search



Business

Product Approval USER: Public User

<u>Product Approval Menu</u> > <u>Product or Application Search</u> > <u>Application List</u> > **Application Detail**

FI# FL15183 Application Type New Code Version 2010 Application Status Approved

Comments Archived

Product Manufacturer UNION CORRUGATING COMPANY

Address/Phone/Email 701 S. KING ST.

FAYETTEVILLE, NC 28301 (910) 483-0479 Ext 241 dpotts@unioncorrugating.com

Authorized Signature Dan Potts

dpotts@unioncorrugating.com

Technical Representative Address/Phone/Email

Quality Assurance Representative

Address/Phone/Email

Roofing Category Subcategory Metal Roofing

Compliance Method Evaluation Report from a Florida Registered Architect or a Licensed Florida

Bala Sockalingam

Professional Engineer

Florida Engineer or Architect Name who developed the

Evaluation Report

Florida License

Quality Assurance Entity Quality Assurance Contract Expiration Date

Validated By

PE-62240

Keystone Certifications, Inc.

12/31/2015 Yoosef Lavi, P.E.

✓ Validation Checklist - Hardcopy Received

Certificate of Independence

FL15183 RO COI CertificateIndependence.pdf

Referenced Standard and Year (of Standard)

Standard Year TAS 125 2003 UL 1897 2004 UL 580 2006

Equivalence of Product Standards

Certified By

Sections from the Code

Product Approval Method Method 1 Option D

Date Submitted 02/10/2012 Date Validated 02/13/2012 Date Pending FBC Approval 02/17/2012 Date Approved

Summary of Products

FL#	Model, Number or Name	Description
15183.1	5V	Min 26 ga., 24" wide through fastened panel over 15/32" or 19/32" thick plywood
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-150 Other: Uplift load of 150 psf in 19/32" thick plywood for Fastener Pattern 2		Installation Instructions FL15183 R0 II D1828 1.pdf Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes Evaluation Reports FL15183 R0 AE EvaluationReportC1828 1.pdf Created by Independent Third Party: Yes
15183.2	Advantage-Lok II	Min 26 ga., 16" wide concealed fastened panel over 7/16" thick OSB & 15/32" & thick plywood
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: N/A Design Pressure: +N/A/-112.5		Installation Instructions FL15183 R0 II D1828 2.pdf Verified By: Bala Sockalingam PE 62240 Created by Independent Third Party: Yes Evaluation Reports
Other: Uplift load of 52.5 psf @ fastener spacing of 6" o.c. and uplift load of 112.5 psf @ fastener spacing of 6" o.c. with structural sealant.		FL15183 RO AE EvaluationReportC1828 2.pdf Created by Independent Third Party: Yes





Contact Us:: 1940 North Monroe Street, Tallahassee FL 32399 Phone: 850-487-1824

The State of Florida is an AA/EEO employer. Copyright 2007-2013 State of Florida. :: Privacy Statement :: Accessibility Statement :: Refund Statement

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click here.

Product Approval Accepts:



