

Peel & Stick Roof Underlayment

MFM Wind & Water Seal™

This 40 mil underlayment is composed of a non-slip cool white/gray polymer film that prevents damage from wind-driven rain. It also is ideal for secondary water resistance and prevents damage from ice dams. The non-slip surface includes overlap guide lines for easy installation. May be left exposed for up to 60 days.

MFM Wind & Water SealTM is available in a roll size of 36" wide x 67' length.





Peel & Stick Roof Underlayment

Non-Slip

Polymer film for superior slip resistance.

Protects

MFM Wind & Water Seal can be left exposed for up to 60 days. This is especially useful when you are unable to install the primary roof immediately afterwards.

Description

MFM Wind & Water Seal™ is a self-adhering waterproofing underlayment composed of a non-slip polymer film laminated to a high temperature rubberized asphalt adhesive. A split release liner protects the adhesive and is removed as the underlayment is installed.



MFM Wind & Water Seal Installed on Air Force Base Roof

Uses

Whole-roof underlayment for shingle, tile, shake, or metal roofing. Use in valleys, ridges, around chimneys and at eaves for protection against ice dams and wind driven rain.

Features

Wind & Water Seal offers the contractor and property owner these extra features:

- Uniform thickness for dependable protection
- Self-seals around fasteners including nails, staples and screws
- High elongation, flexible, accommodates expansion and contraction of the substrate
- Compatible with most construction sealants and primers
- Eliminates leaks multiple layers of protection seal out water
- Rubberized asphalt won't crack or dry protects against wind and rain
- Aggressively adheres to plywood, foam board, metal, vinyl and most other building materials for ease of application and to eliminate movement of water under the membrane
- Non-slip surface and overlap guide lines for easy installation

