


2.5" Corrugated - Roof - Technical Sheet

ROOF PANEL



COMMERCIAL
RESIDENTIAL
PANEL

EXPOSED
FASTENED


$21\frac{1}{3}$ "
COVERAGE

MINIMUM
SLOPE
3:12

OPEN FRAMING OR
SOLID SUBSTRATE

PANEL OVERVIEW

- ▶ Finishes: Painted, Acrylic-Coated Galvalume® and Bare Galvanized
- ▶ Corrosion Protection: AZ55 per ASTM A 792 for unpainted Galvalume®
AZ50 per ASTM A 792 for painted Galvalume®
G60, G90 or G100 per ASTM A 653 for Galvanized
- ▶ Gauges: 30 ga, 29 ga and 26 ga standard; 24 ga and 22 ga optional
- ▶ $21\frac{1}{3}$ " panel coverage, $\frac{1}{2}$ " rib height
- ▶ Panel Length: Minimum: 3'-6"; Maximum: 30' recommended
- ▶ Exposed fastened, low profile roof system
- ▶ Corrugated ribs on $2\frac{2}{3}$ " centers
- ▶ Minimum roof slope: 3:12




TESTING AND APPROVALS

- ▶ UL 2218 Impact Resistance - Class 4
- ▶ UL 790 Fire Resistance Rating - Class A, per building code
- ▶ UL 263 Fire Resistance Rating - per assembly
- ▶ Texas Windstorm Certified
- ▶ Florida Building Code Approved - See Reports for Requirements
- ▶ ICC Evaluation Report - ESR-2385



BEST BUY METALS
Roofing That Lasts

2.5" Corrugated - Roof - Technical Sheet

ATTACHMENT DETAILS



FASTENING PATTERN



FASTENER INFORMATION

Overdriven fasteners will cause panel distortions.

Fasteners should extend 1/2" or more past the inside face of the support material.

Thick panels (ex. 18 ga) or supports (ex. 1/2" steel) may require predrilling of holes for screws.

Panel Fasteners:

Attaching to Wood:

#10-14 Wood Screw

#10-14 XL Wood Screw

Attaching to Steel:

#12-14 Self Drilling Screw

#12-14 XL Self Drilling Screw

Side Lap Fastener:

1/4"-14 x 7/8" Stitch Screw

1/4"-14 x 7/8" XL Stitch Screw

Trim Fastener:

1/4"-14 x 7/8" Stitch Screw

1/4"-14 x 7/8" XL Stitch Screw

SECTION PROPERTIES

Ga	Width in	Yield ksi	Weight psf	Top In Compression		Bottom In Compression	
				Ixx in ⁴ /ft	Sxx in ³ /ft	Ixx in ⁴ /ft	Sxx in ³ /ft
				30	21.33	80	0.66
29	21.33	80	0.70	0.0056	0.0215	0.0056	0.0208
26	21.33	50	0.90	0.0073	0.0275	0.0073	0.0274
24	21.33	50	1.17	0.0096	0.0354	0.0096	0.0354
22	21.33	50	1.53	0.0124	0.0457	0.0124	0.0457

ALLOWABLE UNIFORM LOADS, psf For various fastener spacings

		Inward Load						Outward Load					
		2'		2.5'		3'		2'		2.5'		3'	
		2'	2.5'	3'	3.5'	4'	4.5'	2'	2.5'	3'	3.5'	4'	4.5'
30	21.33	107	55	32	20	14	9	107	55	32	20	14	9
29	21.33	118	60	35	22	15	10	118	60	35	22	15	10
26	21.33	153	78	45	29	19	13	153	78	45	29	19	13
24	21.33	200	102	59	37	25	18	200	102	59	37	25	18
22	21.33	259	133	77	48	32	23	259	133	77	48	32	23

- Theoretical section properties have been calculated per AISI 2012 'North American Specification for the Design of Cold-Formed Steel Structural Members'. Ixx and Sxx are effective section properties for deflection and bending.
- Allowable load is calculated in accordance with AISI 2012 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers the 3 or more equal spans condition. Allowable load does not address web crippling, fasteners, support material or load testing. Panel weight is not considered.
- Deflection consideration is limited by a maximum deflection ratio of L/180 of span.
- Allowable loads do not include a 1/3 stress increase for wind.