

Technical Bulletin #9

EZ-VENTS

Date Issued: September 17, 2004


EZ-Vents

The Boral EZ-Vents are designed to eliminate traditional flashing details that are necessary with most standard large dormer vent installations. The EZ-Vent allows an easy drop-in application and can enhance the overall look of a completed Boral Steel roof, while also dramatically speeding up the process of installing ventilation to a structure. They are available in all Boral Steel profiles and install similar to regular field panels. They interlock and lap just like a standard field panel providing great weather protection.


EZ-Vents Details

Each EZ-Vent incorporates an internal 'Weather Stop' for further security in severe climate conditions and 'Bug Screen' protection that allows free flow of air through the vent.

- **EZ-Vent PINE-CREST Shake**
52" L X 14-1/2" D X 3-1/2" H
NFVA = 72.00Sq. in.




- **EZ-Vent COTTAGE Shingle**
51" L X 14-1/2" D X 3-1/2" H
NFVA = 72.00Sq. in.



- **EZ-Vent GRANITE-RIDGE Shingle**
44" L X 14" D X 3-1/2" H
NFVA = 72.00Sq. in.



- **EZ-Vent PACIFIC Tile**
52" L X 14-1/2" D X 3-1/2" H
NFVA = 72.00Sq. in.



- **EZ-Vent BARREL-VAULT Tile**
47" L X 14" D X 3-1/2" H
NFVA = 72.00Sq. in.



INSTALLATION WARNING:

Apply a **bead of sealant** (NovaFlex type) along the back vertical up stand & horizontal lip of each EZ-Vent. Before installing the ridge panel above, **use #10 X 2" Hex Head screws** (1,000 hour salt spray corrosion resistant type) to secure the nose of the Boral Steel panel above to the EZ-Vent below. To prevent rodents and other vermin from entering the attic space, the roof deck ventilation hole should be covered with 1/4-inch square mesh.

We reserve the right to amend or update these documents at any time.