

FASTENERS:  
USE MIN #9 CORROSION  
RESISTANT SCREWS  
(COLOR COORDINATED  
IN EXPOSED AREAS)

VENT MATERIAL:  
COMPRESS BETWEEN  
PANEL BEND AND  
HIP & RIDGE

SHAKE HIP & RIDGE

BATTENS:  
2" NOMINAL LUMBER  
STACKED AS REQUIRED

DECRA SHAKE XD PANEL:  
BEND UP BACK EDGE 1-1/2"

UNDERLAYMENT

1" MIN OPENING  
BETWEEN HIP &  
RIDGE AND PANEL

SHEATHING: TYP  
MIN 15/32"

CUT 1" GAP IN SHEATHING  
BOTH SIDES

TITLE

Ridge Vent Installation with Center Beam- Shake XD®

DRAWING No.

ARCH2009-5-09a

DECRA ROOFING SYSTEMS, INC.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF  
DECRA ROOFING SYSTEMS, INC. ANY REPRODUCTION IN PART OR IN WHOLE  
WITHOUT PRIOR APPROVAL AND WRITTEN PERMISSION IS PROHIBITED.

1230 RAILROAD ST. CORONA, CA 92882 PH (951)272-8180 Fax (951)272-4476

DATE: 03-18-13

SCALE: 4" = 1' 0"